

## FITTING INSTRUCTIONS FOR CP0186BL CRASH PROTECTORS BMW F800ST '06

Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – the rubber washers should be thrown away!

## Near side (left side as you sit on bike)

- Remove side fairing
- Remove the two top engines to frame M10 diameter bolts. (See picture above)
- Place shorter of the stepped aluminium spacer into front bolt recess.
- Place thinnest spacer into back bolt recess.
- Place shortest M10 cap head bolt with washer into "dog leg" metal spar (marked position 'A') with head and washer into counter-bore.
- Place M10 x 120mm long cap head bolt with washer into "dog leg" metal spar (marked position 'B') with head and washer into counter-bore.
- Fit assembly and tighten as shown above.
- Screw pointed marking tool into central tapped hole. Screw in leave about 15mm proud.
- Offer up fairing with 3-4 fairing screws ensuring point does no damage to fairing.
- Check to see if point is close to inner surface of fairing (cut foam away locally if required)
- By removing and offering up fairing adjust marking tool until it is just clear of fairing so when a slight amount of pressure is applied to fairing the point marks the inside surface of fairing.
- Remove fairing ensuring it is marked properly.
- Using pilot drill of 28mm hole-saw drill drill fairing pilot hole size only.
- Refit fairing ensuring pilot hole lines up with point on marking tool.
- Remove fairing and marking tool.
- Drill fairing from outside with 28mm hole-saw and deburr hole.
- Refit fairing
- Check alignment with M12 hole.
- Place 12mm washer on M12 hex head bolt, fit bolt with washer into bobbin counter bore.
- Fit bobbin and bolt through fairing into M12 hole and tighten (do not exceed 40NM of torque)

<u>Offside</u>, as nearside except using longer stepped spacer, thicker plain spacer and 130mm long cap head bolt instead of 120mm long bolt.

Check all fastenings and indicators before use.



## **CONSUMER NOTICE**

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes.

Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products.

On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect.

Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned.

These terms do not affect the Buyer's statutory rights.

## R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected)

Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor.

Goods must be in re-sellable condition, in the opinion of R&G Racing.

All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase).

The customer must pay any and all carriage charges.

No returns of discontinued products, unless within 14 days of purchase.

This policy does not affect your statutory rights and does not refer to faulty goods.