



FITTING INSTRUCTIONS FOR RAD0205 RADIATOR GUARD
YAMAHA YZF-R25/R3 and MT-03/MT-25 2014-



PICTURE 'A'



PICTURE 'B'

THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED BELOW.
DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away!*

THE PARTS SHOWN MAY BE REPRESENTATIVE ONLY (FOR CLARITY OF INSTRUCTIONS ONLY)

Digital copies of these instructions are available to download from www.rg-racing.com

GENERAL TORQUE SETTINGS

M4 BOLT = 8Nm
 M5 BOLT = 12Nm
 M6 BOLT = 15Nm
 M8 BOLT = 20Nm
 M10 BOLT = 40Nm

TOOLS REQUIRED

- Socket set to include 10 socket and wrench.
 - 4, 5, 6 and 8mm Allen keys.
 - Phillips driver.

In This Kit There Should Be

- 1x Radiator Guard (RAD0205)
- 2x 100mm Lengths of self-adhesive Foam
 - 4 x Cable/Zip Ties.

R&G Racing

Unit 1 Shelleys Lane, East Worldham, Alton, Hants GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Picture 1




Picture 2




Picture 3



Picture 4



Picture 5



Picture 6



Picture 7



Picture 8



Picture 9



Picture 10



Picture 11



Picture 12



Picture 13



Picture 14




Picture 15



Picture 16




Picture 17



Picture 18



Picture 19



Picture 20

FITTING INSTRUCTIONS FOR R25 and R3

Near side (left side as you sit on bike)

- Remove the two bolts arrowed in pictures 1 and 2 and remove the left hand side plastic infill panel.
- Remove the two bolts arrowed in picture 3 and remove the plastic seat/frame panel.
- Remove the bolts and plastic rivets arrowed in pictures 4 thru 9 and carefully remove the left hand side fairing.

Off side (right side as you sit on bike)


- Remove the two bolts arrowed in pictures 11 and 12 and remove the right hand side plastic infill panel.
- Remove the two bolts arrowed in picture 13 and remove the plastic seat/frame panel.
- Remove the bolts and plastic rivets arrowed in pictures 14 thru 16 and carefully remove the right hand side fairing.
- To fit the radiator guard to the bike, cut the foam strip provided into 10mm wide pieces and stick them to the back of the radiator guard frame, so that they sit between the radiator guard and the radiator.
- Remove the two bolts arrowed in pictures 17 and 18.
- Offer the radiator guard into position and secure using the original two bolts on the lower mounting.
- On the upper mounts use the cable ties supplied to secure in position as shown in pictures 19 and 20.
- Refit all the side fairings and panels as original.




Picture 21




Picture 22



Picture 23



Picture 24



Picture 25




Picture 26


R&G Racing

Unit 1 Shelleys Lane, East Worldham, Alton, Hants GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Picture 27



Picture 28




Picture 29



Picture 30



Picture 31



Picture 32

R&G Racing

Unit 1 Shelleys Lane, East Worldham, Alton, Hants GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



FITTING INSTRUCTIONS FOR MT-25 and MT-03

Near side (left side as you sit on bike)

- Remove the two bolts arrowed in pictures 21 and remove the left hand side plastic panel.
- Remove the plastic rivet arrowed in picture 22.
- Remove the two bolts arrowed in picture 23.

Off side (right side as you sit on bike)

- Remove the two bolts arrowed in pictures 24 and remove the left hand side plastic panel.
- Remove the plastic rivet arrowed in picture 25.
- Remove the two bolts arrowed in picture 26.

- Remove the bolt arrowed in picture 27.
- Remove the bolt arrowed in picture 28 and remove the plastic radiator surround.
- Remove the two bolts arrowed in picture 29 and 30.
- Cut the foam strip provided into 10mm wide pieces and stick them to the back of the radiator guard frame, so that they sit between the radiator guard and the radiator.
- Offer the new radiator guard into position and secure in position as shown in pictures 31 and 32, using the original bolts (do not fully tighten at this stage).
- On the upper mounts use the cable ties supplied to secure in position as shown in pictures 19 and 20.
- Tighten the two lower radiator mounting bolts as shown in pictures 29 and 30.
- Refit the plastic radiator surround as original using the original bolts and plastic rivets.
- Refit and tighten the ABS bracket bolt shown in picture 28.
- Refit both plastic side panels as original.

ISSUE 1 14/07/2016 (NSY)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1 Shelleys Lane, East Worldham, Alton, Hants GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



NOTICE DE MONTAGE RAD0205 RADIATOR GUARD
YAMAHA YZF-R25/R3 et MT-03/MT-25 2014-



PHOTO 'A'



PHOTO 'B'

LE KIT CONTIENT LES ARTICLES EXPOSES CI-DESSOUS, VERIFIER QUE TOUTES LES PIECES SOIENT PRESENTES AVANT DE PROCEDER AU MONTAGE.

LA FAÇON DONT LE KIT EST EMBALLE NE CORRESPOND PAS FORCEMENT A LA FAÇON DE MONTER LES PIECES SUR LA MOTO.

LES PARTIES PRESENTEES PEUVENT ETRE UNIQUEMENT REPRESENTATIVES (POUR LA CLARTE DES INSTRUCTIONS UNIQUEMENT)

Notez que si les kits sont emballés avec des rondelles en caoutchouc servant à tenir les composants, *ces rondelles doivent être jetées.*

Notice disponible au téléchargement sur www.rg-racing.com

COUPLES DE SERRAGE RECOMMETES

M4 BOULON = 8Nm
 M5 BOULON = 12Nm
 M6 BOULON = 15Nm
 M8 BOULON = 20Nm
 M10 BOULON = 40Nm

OUTILS REQUIS

- Clé à douille 10.
- Clés Allen 4, 5, 6 et 8mm.
- Tournevis cruciforme.

R&G Racing

Unit 1 Shelleys Lane, East Worldham, Alton, Hants GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Le kit doit contenir :

- 1x Grille de protection radiateur (RAD0205)
 - 2x 100mm Beteaux autocollants
 - 4 x Colliers de serrage.



Photo 1



Photo 2



Photo 3



Photo 4



Photo 5



Photo 6




Photo 7




Photo 8



Photo 9



Photo 10



Photo 11



Photo 12



Photo 13



Photo 14



Photo 15



Photo 16



Photo 17



Photo 18



Photo 19



Photo 20

NOTICE DE MONTAGE POUR R25 et R3

Coté gauche (assis sur la moto)

- Enlever les 2 boulons indiqués sur les photos 1 et 2 puis enlever le panneau interne du coté gauche.
- Enlever les 2 boulons indiqués sur la photo 3 puis enlever le panneau plastic de siège/cadre.
- Enlever les boulons et rivets indiqués sur les photos 4 à 9 puis enlever le carénage du coté gauche.

Coté droit (assis sur la moto)

- Enlever les 2 boulons indiqués sur les photos 11 et 12 puis enlever le panneau interne du coté droit.
- Enlever les 2 boulons indiqués sur la photo 13 puis enlever le panneau plastic de siège/cadre.
- Enlever les boulons et rivets indiqués sur les photos 14 à 16 puis enlever le carénage du coté droit.



- Couper la mousse autocollante en beteaux de 10mm puis collez ces beteaux au bas du support de protection radiateur, de façon à ce que ces beteaux se situent entre la protection radiateur et le radiateur.
- Enlever les 2 boulons indiqués sur les photos 17 et 18.
- Monter la grille de protection en position puis fixer à l'aide des 2 boulons d'origine sur le support de fixation inférieur.
- Sur les supports supérieurs, utiliser les colliers de serrage fournis pour fixer la position, voir photos 19 et 20.
- Remonter tous les carénages latéraux et panneaux comme au départ.




Photo 21



Photo 22




Photo 23




Photo 24




Photo 25



Photo 26




Photo 27




Photo 28




Photo 29



Photo 30

R&G Racing

Unit 1 Shelleys Lane, East Worldham, Alton, Hants GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Photo 31




Photo 32

NOTICE DE MONTAGE POUR MT-25 et MT-03

Coté gauche (assis sur la moto)

- Enlever les 2 boulons indiqués sur les photos 21 et enlever le panneau plastic du coté gauche.
- Enlever le rivet plastic indiqué sur la photo 22.
- Enlever les 2 boulons indiqués sur la photo 23.

Coté droit (assis sur la moto)

- Enlever les 2 boulons indiqués sur la photo 24 et enlever le panneau plastic du coté gauche.
- Enlever le rivet indiqué sur la photo 25.
- Enlever les 2 boulons indiqués sur la photo 26.
- Enlever le boulon indiqué sur la photo 27.
- Enlever le boulon indiqué sur la photo 28 et enlever le contour de radiateur en plastic.
- Enlever les 2 boulons indiqués sur les photos 29 et 30.
- Couper la mousse en bandeaux de 10mm puis collez ces bandeaux au bas du support de protection radiateur, de façon à ce que ces bandeaux se situent entre la protection radiateur et le radiateur.
- Monter la nouvelle grille de protection en position puis fixer comme sur les photos 31 et 32, à l'aide des boulons d'origine (Ne pas serrer au maximum à ce stade).
- Sur les supports supérieurs, utiliser les colliers de serrage fournis pour fixer la position, voir photos 19 et 20.
- Serrer les 2 boulons de fixation inférieur du radiateur, voir photos 29 et 30.
- Remonter le contour radiateur en plastic d'origine, en utilisant les boulons d'origine et rivets.
- Remonter et serrer le boulon de support ABS, voir photo 28.
- Remonter les 2 panneaux latéraux en plastic comme à l'origine.



CONSUMER NOTICE

The catalogue description et any exhibition of samples are only broad indications of the Products et R&G may make design changes which do not diminish their performance or visual appeal et supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation et the Buyer confirms it has chosen the Products as being of merchantable quality et suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill et care et rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions et good engineering practice or if the defect arises from accident or neglect. Other than identified above et subject to R&G not limiting its liability for causing death et personal injury, it shall not be liable for indirect or consequential loss et otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking et handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any et all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights et does not refer to faulty goods.

R&G Racing

Unit 1 Shelleys Lane, East Worldham, Alton, Hants GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com