16703 Antihopping slipper clutch CBR600RR 2007 – mounting instructions

Congratulation, you bought one of best clutch systems for your CBR.

Everytime is better when this operation do an experienced Honda workshop, or mechanic.

- 1. Read this instructions with photos before you start. Check if the set includes all parts.
- 2. Remount the old clutch drum (according Honda workshop manual), clean thread on the shaft from old glue with brake cleaner.
- 3. Put shim (STD) between basket and drum, when you remounted it (pic. a).
- 4. Install slipper drum, be carefull to not the balls jumps out into engine case (fig.b)
- 5. Put the standart steel washers (pic.c). Mount the spider spring (pic.d).
- 6. Fix big nut (kit) with torque 127 Nm and fix it with glue Loctite No. 620. (fig.e, f).
- 7. This slipper clutch is designed for using STD clutch plates. In the STD clutch plates set are thin steel rings there. This rings mount them as first (from case) in STD position (pic. g). Another plates mount as STD (pic. h).
- 8. Put the STD push rod (pic. i)
- 9. Install pressure plate (pic. j)
- 10. Put STD clutch springs in position as before, put spring kit-buckels, fix all with M5 bolts with torque 8 Nm (pic. k)).

Check correct clearance between pressure plate and clutch hub

in bore in pressure plate. Correct clearance is 1.0 mm. In case the clearance is smaller as 0,4, replace all friction plates. In this case change all friction plates to new ones.

11. In case you use aftermarket friction plates, you can reach correct clearance by using Suitable combination of following steel plates:

Order No.	Thickness
Honda	
22321-MAS-000	2.6
22321-MEL-000	2.3
Suzuki	
21451-31E 30	2.6
21451-31E 00	1.6
21451-31E 10	2.0

- 12. Everytime use new clutch cover gasket.
- 13. Mount case cover according to Honda workshop manual.
- 14. Adjust clutch cable

TUNING TIPS

-in case you have strong tuned up engine, and clutch slips by acceleration, use KIT HRC springs + spring buckels 14212

-in case you prefere less engine backtorque, use 1-3 pcs. Honda CBR600RR 2003 - 2006 clutch springs + spring buckels 16206 (from clutch kit 14203)

LIST OF PARTS

1 pc. Two-piece clutch drum

1 pc. spider spring

5 pcs. steel ball

1 pc. pressure plate

5 pcs. spring buckels

5 pcs. bolt M5